# IB BETAFENCE



# Sentinel® Railing Systems

# Versatile railing systems for many applications



## Sentinel® Convex Play

**Convex Play is a CHILD SAFE Bowtop railing system,** specifically designed to meet the safety standards demanded for schools, play and residental areas. The projection of the bow top from the horizontal rail and spacing of the vertical tubes are specifically positioned to avoid the trapping of young children. Panels have a unique custom rolled 'C' section horizontal rail and posts are supplied with a tamper proof aluminium cap. Standard range of heights are available from 1m to 1.5m high.



## Sentinel® Convex Bow Top

**Sentinel Convex Bow Top is a round tube bow top railing system.** Vertical tubes are 25.4mm diameter. Panels have a unique custom rolled 'C' section horizontal rail and a standard range of heights are available from 1.5m to 2.4m high.



## Sentinel® Convex

**Sentinel Convex is a round vertical tube railing system.** Vertical tubes are 25.4mm diameter. The tops of the vertical tubes are supplied with optional flat cut or angle cut profile. Panels have a unique custom rolled 'C' section horizontal rail and a standard range of heights are available from 1.5m to 2.4m high.



## **Sentinel®** Matrix

**Sentinel Matrix is a square vertical tube railing system.** Verticals are 25.4 x 25.4mm square tubes and are positioned diamond to view to give maximum strength and aesthetic appearance. The tops of the vertical tubes are supplied with optional flat cut or angle cut profile. Panels have a unique custom rolled 'C' section horizontal rail and a standard range of heights are available from 1.5m to 2.4m high.



## Sentinel® Gates for Railings

A standard range available in single or double leaf configuration complete with infill tubes to match the spacing and topping of the railing panels. Gates have horizontal top and bottom rails that are located at the same height as railing panels and rails and infill tubes are positioned to match the adjoining system.

Gate posts have inserts inline to accept adjoining panels and are multi drilled to provide the same provision to step as the fence posts. Gates are fitted as standard with lockable ground bolts.

All gates have fully adjustable rear-hung hinges which allow each leaf to swing through 180°. Locking is by means of a mortice lock or slip latch holed for padlocking.

Complete technical advisory service available upon request.

## Standard features

## Sentinel® Panels



All panels widths - 2762mm



The cross rails are a **unique custom rolled** 'C' 60 x 40 x 3mm section.



**Panel supports -** 2 supports are supplied as standard per bay.

## Sentinel® Posts

#### Post Sections



- 1m 1.2m high 60x60x2.0mm
- 1.5m 2.0m high 60x60x2.5mm
- 2.4m high 80x80x2.5mm
- Intermediate posts are bolt through.
- Corner posts are inserted and can be used for internal or external corners.

### Posts are multi drilled as standard for stepping to achieve the following:



)



50mm



100mm



150mm

#### Post toppings



Tamper proof aluminum cap









Decorative 'ball top' aluminum can

## Sentinel® Fixings



#### **Unique plastic insert**

- profiled to match the 'C' section cross rail.
- · designed to reduce 'rattle' and vibration
- allows panels 5° of pivot (approx 250mm across a standard width bay)

Up to 5% pivot either side.





Angle cleats are secured to posts using bolts and shear nuts.



**Trilobe Pilot bolt** secures cross rail and profiled insert to angle cleat.

 Pilot bolts are designed to eliminate 'cross threading'


## Sentinel® Finish

#### Two finishes are available

- Hot dipped galvanised BS EN ISO1461
- Hot dipped galvanised BS EN ISO1461 and
  Polyester powder coated

#### Wide range of standard colours available

Green Black Red Yellow Blue Grey White RAL6005 RAL9005 RAL3020 RAL1006 RAL5010 RAL7037 RAL9010



Specifications (mm)								
Fence Height	Panel Height	Panel Width	Overall Post Length	Tube Diameter	Distance Between Verticals	Projection from Top Rail		
A	B	C	O	<b>(3</b>	G	G		
1000	950	2762	1600	19	85	85		
1200	1150	2762	1800	19	85	85		
1500	1450	2762	2100	19	85	85		



## Sentinel® Finish

#### Two finishes are available

- Hot dipped galvanised BS EN ISO1461
- Hot dipped galvanised BS EN ISO1461 and Polyester powder coated

#### Wide range of standard colours available

Green Black Red Yellow Blue Grey White RAL6005 RAL9005 RAL3020 RAL1006 RAL5010 RAL7037 RAL9010



## **Specifications (mm)**

Fence Height	Panel Height	Panel Width	Overall Post Length	Tube Diameter	Distance Between Verticals	Projection from Top Rail
A	B	C	0	<b>(3</b>	G	G
1500	1450	2762	2100	25.4	96	150
1800	1750	2762	2500	25.4	96	200
2000	1950	2762	2700	25.4	96	200
2400	2350	2762	3100	25.4	96	200




## Sentinel® Finish

#### Two finishes are available

- Hot dipped galvanised BS EN ISO1461
- Hot dipped galvanised BS EN ISO1461 and Polyester powder coated

#### Wide range of standard colours available

Green Black Red Yellow Blue Grey White RAL6005 RAL9005 RAL3020 RAL1006 RAL5010 RAL7037 RAL9010



## Sentinel® Finish

1950

2350

#### Two finishes are available

2000

2400

- Hot dipped galvanised BS EN ISO1461
- Hot dipped galvanised BS EN ISO1461 and Polyester powder coated

2762

2762

2700

3100

25.4

25.4

96


96

#### Wide range of standard colours available

200

200

Green Black Red Yellow Blue Grey White RAL6005 RAL9005 RAL3020 RAL1006 RAL5010 RAL7037 RAL9010



Fence Height	Panel Height	Panel Width	Overall Post Length	Square Tube	Distance Between Verticals	Projection from Top Rail
A	B	C	0	•	•	G
1500	1450	2762	2100	25.4 x 25.4	98	150
1800	1750	2762	2500	25.4 x 25.4	98	200
2000	1950	2762	2700	25.4 x 25.4	98	200
2400	2350	2762	3100	25.4 x 25.4	98	200



## Sentinel® Finish

#### Two finishes are available

- Hot dipped galvanised BS EN ISO1461
- Hot dipped galvanised BS EN ISO1461 and Polyester powder coated

#### Wide range of standard colours available

Green	Black	Red	Yellow	Blue	Grey	White
RAL6005	RAL9005	RAL3020	RAL1006	RAL5010	RAL7037	RAL9010

## IB BETAFENCE

# www.betafence.com



BEKassure is an insurance backed 10-year guarantee covering the supply and installation of Betafence systems.



PRO-net licenced contractors are contractors who are licenced by Betafence to carry out work for the award of a BEKassure 10-year guarantee.

#### **Betafence Limited**

Woodhouse Lane, Wigan, Lancashire WN6 7NS T. 0870 120 3252 F. 0870 120 3242 E. sales.wigan@betafence.com

The Betafence Holding is the European leader in physical perimeter fencing systems and access control.

All Betafence company and product names are trademarks owned by Betafence Holding. Modifications in assortment and products reserved.